HYGROFLEX1



THE INEXPENSIVE **TRANSMITTER**

INNOVATION IN HUMIDITY AND TEMPERATURE MEASUREMENT

- Measures relative humidity and temperature
- Hygromer® IN-1 humidity sensor
- Two freely scalable analog voltage





TECHNICAL INFORMATION

The HygroFlex1 series is the latest development in inexpensive HVAC transmitters for relative humidity and temperature. The devices are equipped with the tried-and-tested Hygromer® IN-1 sensor and boast unbeatable value for money. The optional ROTRONIC HW4 software enables you to change the scale and calibrate and adjust the transmitter.


Dimensions


Wall version (W)





Duct version (D)





General	
Transmitter type	3 / 4-wire
Supply voltage	1228 VAC / 1540 VDC
Current consumption	Transmitter with voltage output: <15 mA Transmitter with current output: <55 mA
Parameters	Humidity and/or temperature
Housing material / IP	ABS / IP65
Weight wall and duct versions	Approx. 140 g
Sensors integrated in device	Yes
Operating and measurement range	050 °C / 595 %RH
CE / EMC compatibility	2004/108/EC
Humidity measurement	
Humidity sensor	ROTRONIC Hygromer® IN-1
Accuracy at 23 °C ±5 K	< 3 %RH (1090 %RH)
Long-term stability	<1.5 %RH per year
Response time τ63	30 s (63 % of a jump 3580 %RH) without filter
Temperature measurement	
Sensor	Thermistor
Standard temperature scale	050 °C or 0100 °F
Accuracy at 23 °C ±5 K	± 0.3 °K (050 °C)
Response time	4 s
Outputs	
Number	Two freely scalable analog outputs
Current	420 mA
Voltage	01/5/10 VDC

Would you like more information?

You can find a complete and up-to-date overview of the HygroFlex1 series on the internet at www.rotronic.com.



59034E/2012-08